

# M Series



### 車輪:

TPU: 尼龍輪殼內包精密滾珠培林，外覆軟質耐磨PU膠，雙面防塵護蓋，轉動靈活，外觀精緻。  
 SR: 一體成型尼龍射出成型，堅韌耐磨，內裝滑動軸套，轉動靈活。

### 輪架:

鐵板沖壓成形，雙排滾珠附防塵圈套活動轉盤設計，旋轉平穩，堅固耐用。

### 剎車:

輪面及活動轉盤同步雙剎車設計，剎車功能佳。

### Wheels:

TPU: polyurethane tread injection moulded, wheel centre of high-quality nylon, and precision ball bearing inside, with sealed dust-free hood

SR(white): high-quality nylon injection-moulded

Bracket: pressed steel, swivel bracket with twin ball race in the swivel head

Brake: wheel and swivel brake stop-top



SM-TPU 100×32



SMK-TPU 100×32



TM-TPU 100×32



TMK-TPU 100×32



TMC-TPU 100×32


TM	TMK	TMC	SM	SMK	材質 MATERIAL	尺寸 SIZE	↓ kg	↑ mm	↑ mm	↑ mm	↑ mm	↑ mm	↑ mm	↑ mm
TM	TMK	TMC	SM	SMK	TPU	3"	80	75	32	105	72×90	53×72	1/2"×25L	
TM	TMK	TMC	SM	SMK	SR	3"	60	75	30	105	72×90	53×72	1/2"×25L	
TM	TMK	TMC	SM	SMK	TPU	4"	120	100	32	138	72×90	53×72	1/2"×25L	
TM	TMK	TMC	SM	SMK	SR	4"	100	100	30	138	72×90	53×72	1/2"×25L	
TM	TMK	TMC	SM	SMK	TPU	5"	130	125	32	165	72×90	53×72	1/2"×25L	
TM	TMK	TMC	SM	SMK	SR	5"	100	125	30	165	72×90	53×72	1/2"×25L	



TPU



SR



可配合底板規格  
for top plate type