

X Series



車輪:

P U:一體成型灌注耐磨膠,內裝滾珠培林,加強荷重,轉動平穩。

TPR:尼龍輪殼,外覆軟質耐磨橡膠,轉動靈活,外觀精緻。

S R:一體成型尼龍射出成型,堅韌耐磨。

輪架:

鐵板沖壓成型,雙排滾珠活動轉盤設計,旋轉平穩,鍍鉻處理,外觀精緻。

剎車:

輪面踏板剎車設計,剎車功能佳。

Wheels:

P U:polyurethane, injection-moulded with twin bearing.

TPR:rubber tread, wheel centre of high-quality nylon.

SR(white):high-quality nylon, injection-moulded.

Bracket:pressed steel, swivel bracket with twin ball bearing race in the swivel head.

Brake:wheel brake stop-top.



TXK-PU 50×22



TXC-PU 50×22



TX-PU 50×22



SX-PU 50×22



SXX-PU 50×22

					材質 MATERIAL	尺寸 SIZE							
TX	TXK	TXC	SX	SXX			kg	mm	mm	mm	mm	mm	mm
TX	TXK	TXC	SX	SXX	SR	1"	20	25	12	35	30×35	24×28	3/8"×20L
TX	TXK	TXC	SX	SXX	PU	2"	40	50	22	67	50×50	38×38	3/8"×20L
TX	TXK	TXC	SX	SXX	SR	2"	30	50	22	67	50×50	38×38	3/8"×20L
TX	TXK	TXC	SX	SXX	TPR	2"	30	50	20	70	50×50	38×38	3/8"×20L
TX	TXK		SX	SXX	TPR	3"	30	75	22	97	42×63	32×52	3/8"×25L
TX	TXK		SX	SXX	SR	3"	30	75	22	97	42×63	32×52	3/8"×20L



PU



TPR



SR