

F Series



車輪:

PR: 充氣式內外胎，內裝鋼圈及精密培林
GR: 胎紋實心橡膠，內裝鋼圈及精密培林。

輪架:

鐵板燒焊結構，珠槽式活動轉盤，轉動平穩，堅固耐用。

剎車:

踏板式輪面剎車設計，剎車功能佳。

Wheels:

PG with ribbed or zig-zag pattern, with inner trbe.

FG: with ribbed or zig-zag pattern, solid rubber

* pressed steel rims, bolted or welded, with precision ball bearing

Bracket: thick steel-welded construction, lacquered, ball race in the swivel head.

Brake: wheel brake stop-top



FC - PR 3.00-4



FK - PR 3.00-4



F - PR 3.00-4

圖示	圖示	圖示	材質 MATERIAL	尺寸 SIZE	kg	mm	mm	mm	mm	mm	mm
F	FK	FC	PR	2.50-4	200	210	55	250	100×140	75×120	12
F	FK	FC	GR	2.50-4	200	210	55	250	100×140	75×120	12
F	FK	FC	PR	3.50-4	250	260	80	300	130×170	105×140	12
F	FK	FC	GR	3.50-4	250	260	80	300	130×170	105×140	12
F	FK	FC	PR	3.50-6	350	310	90	350	130×170	105×140	12



PR(充氣輪)



GRI 橡膠實心輪