

荷重避震輪 Spring-Loaded Wheel

Wheel- ϕ x tread width	Load capacity	Spring tension	Pretension loading	Total height	Top plate size	Bolt hole spacing	Bolt hole- ϕ	Range of spring tension f	Reference no.
輪胎接地寬度 mm	承載重量 kg	彈簧張力 kg	預期承載重量 kg	總高度 mm	方盤尺寸 mm	螺絲孔距 mm	螺絲尺寸 mm	彈簧壓縮範圍 mm	編號

旋轉式腳輪 Swivel Castors

150x50	350	350	50	226	174x114	140x 67	11	25	
200x50	450	350	50	256	174x114	140x 67	11	25	
200x80	600	400	50	275	200x160	160x120	14	45	
250x80	675	800	100	335	200x160	160x120	14	45	
300x90	900	1200	150	380	200x160	160x120	14	45	

固定式腳輪 Fixed Castors

150x50	350	350	50	226	174x114	140x 67	11	25	
200x50	450	350	50	256	174x114	140x 67	11	25	
200x80	600	400	50	275	200x160	160x120	14	45	
250x80	675	800	100	335	200x160	160x120	14	45	
300x90	900	1200	150	380	200x160	160x120	14	45	

- 功能:**
1. 避震
 2. 低噪音
 3. 壽命長
 4. 適用各式牽引子車
 5. 減低物品搬運時之損壞率

- 用途:**
1. 汽車廠
 2. 紡織廠
 3. 航空公司

- Functions:**
1. Absorber
 2. Low noise
 3. Long life
 4. Suitable for all types of tractive trailers.
 5. Reduction of damage for moving.

- Uses:**
1. Automobile factories
 2. Textile factories
 3. Airline companies

